



interdive

DIVE CONTROL

SPECIFICATION SHEET

Tel: +44(0)1803 311222
email: info@interdive.co.uk
website: www.interdive.co.uk

ZONE II RATED DIVE CONTROL

CONTAINER SPECIFICATIONS

Container ID:	12059
Length:	4,880mm
Length when doors open:	5,830mm
Length with escape door open:	5680mm
Width:	2,440mm
Height:	2,760mm
Weight (gross):	10,000Kg
Weight (tare):	6,000Kg

A60 ZONE II DIVE CONTROL CONTAINER

Container built to DNV2.7-1 / BS EN 12079
Access / Escape
One of A60 personnel door
A60 escape hatch fitted with panic bar
Safety features
Full pressurisation
Fire and gas detection shut down
Automatic shutdown
Ventillation and Air conditioning
Emergency lighting
JCE CPFG 3000 series for purge system
JCE IUPS101 back up power supply
Electrical
Transformer
EEx hook up power junction box
transit box

ELECTRICAL SPECIFICATION

Power Inlet:	63amp 440v 3Phw
Cable:	25m core armoured BS6883
Transformer:	15Kva, input 440v output 240v 110v
Outlets:	(decompression chamber supply)



DIVE CONTROL, PANEL / RACK

3 Diver panel with gas analysis
Primary 3 diver communication unit (Fathoms Systems)
Secondary 3 diver communication unit (Fathoms Systems)
Emergency air supply panel
UPS (6 hours run time)
High definition 19" monitor x 5
Hot water alarm
Black box recorder
2 diver hat light and camera controller (Fathoms Systems)

CONTAINER FEATURES

Air conditioning
Recessed penetration plate
Single personnel door
Ambient analyser
Cable trays

DIVE CONTROL SPARES

Black box recorder
O2 analyser
O2 cells
19" monitor
Depth gauge
Indicating gauges
Tescom regulator seal kit
Supervisors headset c/w mic

DIVE CONTROL SUPPLIES

Inspection suite
First aid kit
Emergency deck communications (Peli case)
Deck CCTV cameras
Stationery
Wall mounted PC
3 in 1 printer
2 chairs
Whiteboard
BIBS for Dive Supervisor (AGA)
Portable fire extinguisher