



interdive

Launch And Recovery System (LARS)

SPECIFICATION SHEET

Tel: +44(0)1803 311222
email: info@interdive.co.uk
website: www.interdive.co.uk

Launch And Recovery System (LARS)

AIR DIVING A-FRAME SKID

Length (when closed):	3,500mm
Base length:	3,510mm
Width:	2,040mm
Height (when closed w/o basket):	2,030mm
Max height:	4,820mm
Mass:	5,300Kg
Mass Extension:	450mm at base front
Lifting Padeyes SWL:	3,600Kg
Width Between Arms:	2,267mm
Height to main padeyes:	4,000mm
Hanging Points on Arm:	3 x 1,450 Kg, 2 x 100Kg

CLUMP WEIGHT

Length:	1,380mm
Mass:	300Kg
Height:	300mm
Width:	220mm



BASKET

Length:	1,100mm
Width:	1,300mm
Height:	2,340mm
Mass (tare):	300Kg
Mass (net):	700Kg
Mass (gross):	1,000Kg

MAN RIDING BASKET WINCH SPECIFICATION

Winch:	1 off Ingersol Rand FA2i MR 16MK1G-E
Man-riding rating:	1,450Kg
Drum length:	406mm
Drum brake:	manual
Disc brake:	Yes
Control:	1 winch mounted lever
Rated operating pressure:	6.3 Bar
Air consumption rate: (at rated pressure and load)	10m ³ /min
Full drum line pull:	2,000Kg
Mid drum line speed:	17m/min
Max stall pull:	4,218Kg
Max freeboard:	26mm
Net weight:	430Kg
Drum barrell diameter:	273mm
Wire rope diameter:	13mm
Wire rope length:	120m
Max Depth:	50m

MAN RIDING CLUMP WINCH SPECIFICATION

Winch:	1 off Ingersol Rand FA2.5i MR24MK1G-E
Man-riding rating:	1,450Kg
Drum length:	406mm
Drum brake:	Manual
Disc brake:	Yes
Control:	1 winch mounted lever
Rated operating pressure:	6.3 Bar
Air consumption rate: (at rated pressure and load)	20m ³ /min
Full drum line pull:	2,268Kg
Mid drum line speed:	44m/min
Max stall pull:	4,218Kg
Max freeboard:	26mm
Net weight:	430Kg
Drum barrell diameter:	273mm
Wire rope diameter:	13mm
Wire rope length:	120m
Max Depth:	50m